



LC29H (BA,CA,DA,EA)

DR&RTK Application Note

GNSS Module Series

Version: 1.1

Date: 2023-04-27

Status: Released



At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local offices. For more information, please visit:

<http://www.quectel.com/support/sales.htm>.

For technical support, or to report documentation errors, please visit:

<http://www.quectel.com/support/technical.htm>.

Or email us at: support@quectel.com.

Legal Notices

We offer information as a service to you. The provided information is based on your requirements and we make every effort to ensure its quality. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an "as available" basis. We may revise or restate this document from time to time at our sole discretion without any prior notice to you.

Use and Disclosure Restrictions

License Agreements

Documents and information provided by us shall be kept confidential, unless specific permission is granted. They shall not be accessed or used for any purpose except as expressly provided herein.

Copyright

Our and third-party products hereunder may contain copyrighted material. Such copyrighted material shall not be copied, reproduced, distributed, merged, published, translated, or modified without prior written consent. We and the third party have exclusive rights over copyrighted material. No license shall be granted or conveyed under any patents, copyrights, trademarks, or service mark rights. To avoid ambiguities, purchasing in any form cannot be deemed as granting a license other than the normal non-exclusive, royalty-free license to use the material. We reserve the right to take legal action for noncompliance with abovementioned requirements, unauthorized use, or other illegal or malicious use of the material.

Trademarks

Except as otherwise set forth herein, nothing in this document shall be construed as conferring any rights to use any trademark, trade name or name, abbreviation, or counterfeit product thereof owned by Quectel or any third party in advertising, publicity, or other aspects.

Third-Party Rights

This document may refer to hardware, software and/or documentation owned by one or more third parties ("third-party materials"). Use of such third-party materials shall be governed by all restrictions and obligations applicable thereto.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing or usage of trade.

Privacy Policy

To implement module functionality, certain device data are uploaded to Quectel's or third-party's servers, including carriers, chipset suppliers or customer-designated servers. Quectel, strictly abiding by the relevant laws and regulations, shall retain, use, disclose or otherwise process relevant data for the purpose of performing the service only or as permitted by applicable laws. Before data interaction with third parties, please be informed of their privacy and data security policy.

Disclaimer

- a) We acknowledge no liability for any injury or damage arising from the reliance upon the information.
- b) We shall bear no liability resulting from any inaccuracies or omissions, or from the use of the information contained herein.
- c) While we have made every effort to ensure that the functions and features under development are free from errors, it is possible that they could contain errors, inaccuracies, and omissions. Unless otherwise provided by valid agreement, we make no warranties of any kind, either implied or express, and exclude all liability for any loss or damage suffered in connection with the use of features and functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage may have been foreseeable.
- d) We are not responsible for the accessibility, safety, accuracy, availability, legality, or completeness of information, advertising, commercial offers, products, services, and materials on third-party websites and third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2023. All rights reserved.

About the Document

Document Information

Title	LC29H (BA,CA,DA,EA) DR&RTK Application Note
Subtitle	GNSS Module Series
Document Type	Application Note
Document Status	Released

Revision History

Version	Date	Description
-	2022-02-25	Creation of the document
1.0	2022-09-19	<p>First official release</p> <ol style="list-style-type: none">1. Added applicable module LC29H (EA).2. Added an overview on DR (Chapter 1.1).3. Changed the driving speed of more than 3 m/s to 2 m/s in step 4 of DR calibration, updated the testing scenarios in open sky area, urban main road, and added a note about scenarios where the module exits DR mode (Chapter 2.1.3).4. Added PQTMCFGDRRTD, PQTMCFGIMUTC, PQTMDRPVA, PQTMCFGDRHOT and PQTMCFGDR commands (Chapters 3.1.12, 3.1.13, 3.1.14, 3.1.15 and 3.1.16).
1.1	2023-04-27	

Contents

About the Document	4
Contents	5
Table Index	7
Figure Index	8
1 Introduction	9
1.1. Overview on DR	9
2 Configuration.....	10
2.1. DR Configuration.....	10
2.1.1. Orientation.....	10
2.1.2. Mounting.....	11
2.1.3. DR Calibration.....	12
2.2. RTK Configuration.....	14
2.2.1. RTCM Input.....	14
3 DR Related Messages.....	15
3.1. PQTM Messages	15
3.1.1. PQTMDRCAL.....	15
3.1.2. PQTMIMUTYPE	16
3.1.3. PQTMVEHMSG	17
3.1.3.1. If <MsgType> = 1	18
3.1.3.2. If <MsgType> = 2	18
3.1.3.3. If <MsgType> = 3	19
3.1.3.4. If <MsgType> = 4	20
3.1.4. PQTMSAVEPAR	21
3.1.5. PQTMRESTOREPAR	22
3.1.6. PQTMINS	22
3.1.7. PQTMIMU	24
3.1.8. PQTMGPS	25
3.1.9. PQTMCFGGEINSMSG.....	26
3.1.10. PQTMVEHMOT	28
3.1.11. PQTMSENMSG	29
3.1.11.1. If <MsgVer> = 4	29
3.1.12. PQTMCFGDRRTD.....	30
3.1.13. PQTMCFGIMUTC	31
3.1.14. PQTMDRPVA.....	32
3.1.15. PQTMCFGDRHOT	34
3.1.16. PQTMCFGDR	35
3.2. PAIR Messages.....	37
3.2.1. Packet Type: 6010 PAIR_CUSTOM_SET_MSG_OUTPUT	37
3.2.2. Packet Type: 6011 PAIR_CUSTOM_GET_MSG_OUTPUT	38

4	Appendix A References.....	40
5	Appendix B Special Characters	41

Table Index

Table 1: Supported RTCM Input Messages	14
Table 2: Error Codes	15
Table 3: Related Documents	40
Table 4: Terms and Abbreviations	40
Table 5: Special Characters	41

Figure Index

Figure 1: Reference Frame	10
Figure 2: Module Orientation.....	11
Figure 3: Module Mounting Example	12

1 Introduction

This document describes the dead reckoning (DR) and real-time kinematic (RTK) features, including DR and RTK configurations and DR related messages for Quectel LC29H (BA), LC29H (CA), LC29H (DA) and LC29H (EA) modules. The features supported by each module are as follows:

- LC29H (BA) supports DR and RTK.
- LC29H (CA) only supports DR.
- LC29H (DA) only supports RTK (update rate: 1 Hz).
- LC29H (EA) only supports RTK (update rate: 1–10 Hz, 10 Hz by default).

1.1. Overview on DR

LC29H (BA) and LC29H (CA) support two DR modes: ADR (Automotive Dead Reckoning) and UDR (Untethered Dead Reckoning). In ADR mode, the module relies on speed data from the vehicle and the onboard 6-axis sensor for enhanced accuracy in environments with nonexistent GNSS coverage. The UDR mode does not require speed data. The firmware automatically switches to UDR mode if no speed data is injected upon module power-up.

The module obtains vehicle speed data through wheel-ticks or direct vehicle speed data output (m/s). There are two wheel-tick injection methods: 1) injection through the WHELTICK pin (See [document \[1\] hardware design](#)), with a maximum distance increment of 0.05 m per pulse; 2) cumulative wheel-tick injection through the UART interface (See [Chapter 3.1.3.2 If <MsgType> = 2](#) for the command), with a minimum injection frequency of 10 Hz, and a maximum distance increment of 0.05 m per pulse. The direct vehicle speed output can only be injected through the UART interface, with the minimum injection frequency of 20 Hz, and the maximum error of 0.1 m/s between the injected speed and actual speed. Ensuring a stable vehicle speed injection is crucial, as any interruption during driving will affect performance.

2 Configuration

2.1. DR Configuration

2.1.1. Orientation

The LC29H (BA) and LC29H (CA) modules are designed to work on two-wheel or four-wheel vehicles. Both modules integrate an IMU as well as the GNSS receiver. Therefore, you must ensure that the device incorporating the module is firmly fixed to vehicle body. No relative movement is allowed between vehicle and device and maximum isolation from shock or vibration must be applied. Manually holding the device is not acceptable. The best way to guarantee good installation is to firmly screw the device down to the vehicle frame. Mounting location should permit easy access to power supply and GNSS antenna, and should not be exposed to excessive heat.

Definitions of reference frame axes:

- X-axis points towards the right of the vehicle.
- Y-axis points towards the front of the vehicle.
- Z-axis points towards the roof of the vehicle.




Figure 1: Reference Frame

Module orientation is shown below:




Figure 2: Module Orientation

NOTE

Firmly affix the device incorporating the module to vehicle body. Select a structurally sound location that is not prone to flexing (bending motion of vehicle chassis).

2.1.2. Mounting

There are no mounting direction and angle limitations for mounting the Quectel LC29H (BA) or LC29H (CA) module on the vehicle. The reference model is as follows:




Figure 3: Module Mounting Example

2.1.3. DR Calibration

The module needs to be calibrated before the DR functionality will be useful.

The DR calibration steps are as listed below:

- Step 1:** Fix the device incorporating the module on the vehicle frame firmly. Any displacement, rotation or tilt of the device relative to vehicle plane, however small, may cause performance issues and/or void the calibration.
- Step 2:** Calibration should be performed under good GNSS signal and clear sky conditions.
- Step 3:** Power up the module, then start the vehicle on a plain surface.

Step 4: Drive at a speed of more than 2 m/s, and perform 3–4 turning movements. The module will start self-calibration, which will be completed in approximately 3 minutes.

Step 5: The calibration process ends when **<CalState>** of **\$PQTMDRCAL** message value is 2 (DR is fully calibrated). See [Chapter 3.1.1 PQTMDRCAL](#) for details about the message.

After the calibration, there is no limit to driving trajectory and driving dynamics. You can perform verification tests in the following scenarios:

- 1) Open sky area, urban main road (C/N_0 value is greater than 30 dB-Hz, and the number of satellites is greater than 12).
- 2) Tunnels (assessment of DR performance in absence of satellite visibility).
- 3) Viaduct (assessment of DR performance in weak signal conditions).
- 4) Underground vehicle parking (DR performance in satellite signal absence).
- 5) Areas surrounded with dense buildings (multi-path signals with limited sky view).
- 6) City boulevards (weak satellite signals).
- 7) Urban canyon (high multi-path signals with limited sky view).

NOTE

1. If the wheel speed sensor of the vehicle is connected to the module, make sure that its precision is at least 0.05 m/tick.
2. The module will exit GNSS + DR or DR only mode in the following scenarios:
 - No speed data injection for 5 seconds in ADR mode;
 - Handling scenario;
 - High-speed elevator scenario;
 - IMU data interruption;
 - Inadequate inertial navigation calibration before entering a tunnel or underground garage;
 - Exceeding the set running time or distance of the receiver in environments with nonexistent GNSS coverage (See [Chapter 3.1.12 PQTMCFGDRRTD](#)).

2.2. RTK Configuration

2.2.1. RTCM Input

Quectel LC29H (BA), LC29H (DA) and LC29H (EA) modules support the RTCM 10403.3 input messages listed in the table below.

Table 1: Supported RTCM Input Messages

Message Type	Description
1005	Stationary RTK Reference Station ARP
1006	Stationary RTK Reference Station ARP with Antenna Height
1074	GPS MSM4
1077	GPS MSM7
1084	GLONASS MSM4
1087	GLONASS MSM7
1094	Galileo MSM4
1097	Galileo MSM7
1114	QZSS MSM4
1117	QZSS MSM7
1124	BDS MSM4
1127	BDS MSM7

3 DR Related Messages

3.1. PQTM Messages

This chapter outlines the Quectel DR related PQTM (proprietary NMEA) messages supported by the Quectel LC29H (BA) and LC29H(CA) modules.

Table 2: Error Codes

Field	Format	Unit	Description
<ErrCode>	Numeric	-	Error code. 1 = Invalid parameters. 2 = Execution failed.

3.1.1. PQTMDRCAL

Indicates the DR calibration state.

Type:

Output

Synopsis:

```
$PQTMDRCAL,<MsgVer>,<CalState>,<NavType>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgVer>	Numeric	-	Message version. 1 = Version 1 (Always 1 for this version.)
<CalState>	Numeric	-	DR calibration state. 0 = Not calibrated 1 = DR is lightly calibrated 2 = DR is fully calibrated
<NavType>	Numeric	-	Navigation type.

Field	Format	Unit	Description
			0 = No position
			1 = GNSS only
			2 = DR only
			3 = Combination (GNSS + DR)

Example:

```
$PQTMDRCAL,1,0,1*5C
```

3.1.2. PQTIMUTYPE

Outputs the IMU type once after each boot-up.

Type:

Output

Synopsis:

```
$PQTIMUTYPE,<MsgVer>,<Type>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgVer>	Numeric	-	Message version. 1 = Version 1 (Always 1 for this version.)
<Type>	Numeric	-	IMU type. 0 = IMU error 1 = LSM6DSR 2 = ICM-40608 3 = BMI160 4 = ICM-42670-P

Example:

```
$PQTIMUTYPE,1,2*52
```

3.1.3. PQTMVEHMSG

Inputs/outputs vehicle information.

Type:

Input/output

Synopsis:

```
$PQTMVEHMSG,<MsgType>,<Timestamp>,<Par1>[,<Par2>,...,<ParN>]*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgType>	Numeric	-	Type of message input/output via UART interface. 1 = Vehicle speed (in m/s) 2 = Cumulative wheel tick 3 = Speeds of four wheels (in m/s) 4 = Cumulative wheel ticks of four wheels
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer. Always 0 when this message is input.
<Par1> to <ParN>	Numeric	-	Vehicle information. This field varies with the message type. See Chapter 3.1.3.1 If <MsgType> = 1 to 3.1.3.4 If <MsgType> = 4 for details.

NOTE

<MsgType> can only be 2 for LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.3.1. If <MsgType> = 1

Synopsis:

```
$PQTMVEHMSG,1,<Timestamp>,<VehSpeed>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer. Always 0 when this message is input.
<VehSpeed>	Numeric	m/s	Speed. Range: -100 to 100.

Result:

Returns the input vehicle speed with timestamp:

```
$PQTMVEHMSG,1,<Timestamp>,<VehSpeed>*<Checksum><CR><LF>
```

Example:

```
//Input:  
$PQTMVEHMSG,1,0,3.6*1C  
//Output:  
$PQTMVEHMSG,1,3748292,3.6*1D
```

3.1.3.2. If <MsgType> = 2

Synopsis:

```
$PQTMVEHMSG,2,<Timestamp>,<WheelTickCNT>,<FWD_Ind>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer. Always 0 when this message is input.
<WheelTickCNT>	Numeric	Tick	Cumulative wheel ticks.
<FWD_Ind>	Numeric	-	Forward/backward indicator. 0 = Invalid state 1 = Forward 2 = Backward

Result:

Returns the input cumulative wheel ticks with timestamp:

```
$PQTMVEHMSG,2,<Timestamp>,<WheelTickCNT>,<FWD_Ind>*<Checksum><CR><LF>
```

Example:

```
//Input:  
$PQTMVEHMSG,2,0,100,1*18  
//Output:  
$PQTMVEHMSG,2,153954,100,1*27
```

NOTE

1. When inputting cumulative wheel ticks through UART interface, make sure the input rate is at least 10 Hz.
2. For LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles:
 - 1) Keep **<FWD_Ind>** always 1;
 - 2) **\$PQTMVEHMSG** will not be returned, but the input **<WheelTickCNT>** can be found in **\$PQTMIMU**.

Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.3.3. If <MsgType> = 3**Synopsis:**

```
$PQTMVEHMSG,3,<Timestamp>,<LF_Spd>,<RF_Spd>,<LR_Spd>,<RR_Spd>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<TimeStamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer. Always 0 when this message is input.
<LF_Spd>	Numeric	m/s	Left front wheel speed. Range: -100 to 100.
<RF_Spd>	Numeric	m/s	Right front wheel speed. Range: -100 to 100.
<LR_Spd>	Numeric	m/s	Left rear wheel speed. Range: -100 to 100.
<RR_Spd>	Numeric	m/s	Right rear wheel speed. Range: -100 to 100.

Result:

Returns the input speeds of four wheels with timestamp:

```
$PQTMVEHMSG,3,<Timestamp>,<LF_Spd>,<RF_Spd>,<LR_Spd>,<RR_Spd>*<Checksum><CR><LF>
```

Example:

```
//Input:  
$PQTMVEHMSG,3,0,3.6,3.6,3.6,3.6*19  
//Output:  
$PQTMVEHMSG,3,3748292,3.6,3.6,3.6,3.6,3.6*18
```

3.1.3.4. If <MsgType> = 4**Synopsis:**

```
$PQTMVEHMSG,4,<Timestamp>,<LF_TickCNT>,<RF_TickCNT>,<LR_TickCNT>,<RR_TickCNT><FW  
D_Ind>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer. Always 0 when this message is input.
<LF_TickCNT>	Numeric	Tick	Left front wheel tick count.
<RF_TickCNT>	Numeric	Tick	Right front wheel tick count.
<LR_TickCNT>	Numeric	Tick	Left rear wheel tick count.
<RR_TickCNT>	Numeric	Tick	Right rear wheel tick count.
<FWD_Ind>	Numeric	-	Forward/backward indicator. 0 = Invalid state 1 = Forward 2 = Backward

Result:

Returns the input cumulative wheel ticks of four wheels with timestamp:

```
$PQTMVEHMSG,4,<Timestamp>,<LF_TickCNT>,<RF_TickCNT>,<LR_TickCNT>,<RR_TickCNT><FW  
D_Ind>*<Checksum><CR><LF>
```

Example:

```
//Input:  
$PQTMVEHMSG,4,0,100,100,100,100,100,1*03  
//Output:  
$PQTMVEHMSG,4,153954,100,100,100,100,100,1*3C
```

3.1.4. PQTMSAVEPAR

Saves the configurations set via **\$PQTM** commands or **\$PAIR6010** into NVM. Reset the module after executing this command.

Type:

Command

Synopsis:

```
$PQTMSAVEPAR*<Checksum><CR><LF>
```

Parameter:

None

Result:

- If successful, the module returns:

```
$PQTMSAVEPAR,OK*72
```

- If failed, the module returns:

```
$PQTMSAVEPAR,ERROR,<ErrCode>*<Checksum><CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
$PQTMSAVEPAR*5A  
$PQTMSAVEPAR,OK*72
```

3.1.5. PQTMRESTOREPAR

Restores all DR related configurations to default values.

Type:

Command

Synopsis:

```
$PQTMRESTOREPAR*<CR><LF>
```

Parameter:

None

Result:

- If successful, the module returns:

```
$PQTMRESTOREPAR,OK*3B
```

- If failed, the module returns:

```
$PQTMRESTOREPAR,ERROR,<ErrCode>*<CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
$PQTMRESTOREPAR*13  
$PQTMRESTOREPAR,OK*3B
```

3.1.6. PQTMINS

Outputs navigation results.

Type:

Output

Synopsis:

```
$PQTMINS,<Timestamp>,<SolType>,<Lat>,<Lon>,<Height>,<VEL_N>,<VEL_E>,<VEL_D>,<Roll>,<Pitch>,<Heading>*<CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer.
<SolType>	Numeric	-	Solution type. 0 = DR not ready. Roll and pitch ready. 1 = DR not ready. GNSS, roll, pitch, and relative heading ready. 2 = GNSS + DR mode. DR calibrated. 3 = DR only mode.
<Lat>	Numeric	Degree	Latitude.
<Lon>	Numeric	Degree	Longitude.
<Height>	Numeric	Meter	Height.
<VEL_N>	Numeric	m/s	Northward velocity.
<VEL_E>	Numeric	m/s	Eastward velocity.
<VEL_D>	Numeric	m/s	Downward velocity.
<Roll>	Numeric	Degree	Roll angle.
<Pitch>	Numeric	Degree	Pitch angle.
<Heading>	Numeric	Degree	Heading angle.

Example:

```
$PQTMINS,240951,1,31.82222216,117.11578436,62.555605,-0.004233,0.005535,-
0.004011,0.00,0.00,127.41*40
```

NOTE

1. All angles are scaled from -180.0 to 179.9 with a wrap-around to 0.0 at +180.0. -180/ +180 = South, 0.0 = North, +90.0 = East, and -90.0 = West.
2. This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.7. PQTMIMU

Outputs the IMU raw data: acceleration, angular rate, and hardware wheel ticks. These values should match vehicle frame, and see [Figure 1: Reference Frame](#) for details.

Type:

Output

Synopsis:

```
$PQTMIMU,<Timestamp>,<ACC_X>,<ACC_Y>,<ACC_Z>,<AngRate_X>,<AngRate_Y>,<AngRate_Z>,<WheelTickCNT>,<LastTick_Timestamp>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer.
<ACC_X>	Numeric	m/s ²	Acceleration in X-axis direction.
<ACC_Y>	Numeric	m/s ²	Acceleration in Y-axis direction.
<ACC_Z>	Numeric	m/s ²	Acceleration in Z-axis direction.
<AngRate_X>	Numeric	deg/s	Angular rate in X-axis direction.
<AngRate_Y>	Numeric	deg/s	Angular rate in Y-axis direction.
<AngRate_Z>	Numeric	deg/s	Angular rate in Z-axis direction.
<WheelTickCNT>	Numeric	Tick	Cumulative wheel ticks.
<LastTick_Timestamp>	Numeric	Millisecond	Last tick timestamp.

Example:

```
$PQTMIMU,45454,-1.356730,-0.210568,9.757930,0.564879,0.549612,-0.412209,0,0*77
```

NOTE

This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.8. PQTMGPS

Outputs the position status in GNSS only mode.

Type:

Output

Synopsis:

```
$PQTMGPS,<Timestamp>,<TOW>,<Lat>,<Lon>,<Altitude>,<Speed>,<Yaw>,<Accuracy>,<HDOP>,<PDOP>,<NumSatUsed>,<FixMode>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Timestamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer.
<TOW>	Numeric	Second	Time of week.
<Lat>	Numeric	Degree	Latitude.
<Lon>	Numeric	Degree	Longitude.
<Altitude>	Numeric	Meter	Altitude.
<Speed>	Numeric	m/s	Ground speed (two-dimensional).
<Yaw>	Numeric	Degree	Heading of vehicle (two-dimensional).
<Accuracy>	Numeric	Meter	Horizontal accuracy estimate.
<HDOP>	Numeric	-	Horizontal dilution of precision.
<PDOP>	Numeric	-	Position dilution of precision.
<NumSatUsed>	Numeric	-	Number of satellites used in navigation.
<FixMode>	Numeric	-	Fix mode. 0 = No fix 2 = 2D fix 3 = 3D fix

Example:

```
$PQTMGPS,86139,94183,31.82218794,117.11579022,65.755080,0.027,94.68,2.533952,0.555471,0.88
6183,29,3*6B
```

NOTE

This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.9. PQTMCFGEINSMMSG

Sets/get \$PQTMINS, \$PQTMIMU and \$PQTMGPS message configurations.

Type:

Set/get

Synopsis:

```
//Set message configurations:  
$PQTMCFGEINSMMSG,<Type>,<INS_Enabled>,<IMU_Enabled>,<GPS_Enabled>,<Rate>*<Checksum>  
<CR><LF>  
//Get message configurations:  
$PQTMCFGEINSMMSG,<Type>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Type>	Numeric	-	Set/get message configurations. 0 = Get 1 = Set
<INS_Enabled>	Numeric	-	Enable/disable the output of \$PQTMINS message. 0 = Disable 1 = Enable
<IMU_Enabled>	Numeric	-	Enable/disable the output of \$PQTMIMU message. 0 = Disable 1 = Enable
<GPS_Enabled>	Numeric	-	Enable/disable the output of \$PQTMGPS message. 0 = Disable 1 = Enable
<Rate>	Numeric	Hz	Set the output rate of \$PQTMINS, \$PQTMIMU or \$PQTMGPS message. It can be set to 1, 2, 4, 5, 10, 20, 50, or 100. For \$PQTMGPS, the output rate is fixed at 1 Hz. For \$PQTMINS, when <Rate> is set to be greater than 10, the message will be output at 10 Hz.

Result:

- If successful, the module returns:

```
//Set:  
$PQTMCFGEGINMSGOK*16  
//Get:  
$PQTMCFGEGINMSG,<Type>,<INS_Enabled>,<IMU_Enabled>,<GPS_Enabled>,<Rate>*<Checksum>  
<CR><LF>
```

- If failed, the module returns:

```
$PQTMCFGEGINMSGERROR*4A
```

Example:

```
//Set message configurations:  
$PQTMCFGEGINMSG,1,1,1,1,10*3F  
$PQTMCFGEGINMSGOK*16  
//Get message configurations:  
$PQTMCFGEGINMSG,0*0E  
$PQTMEINMSG,0,1,1,1,10*3E
```

NOTE

1. Send **\$PQTMSAVEPAR*5A** and reset the module for **\$PQTMCFGEGINMSG** to take effect.
2. This command is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for two-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.10. PQTMVEHMOT

Outputs vehicle motion information after DR calibration.

Type:

Output

Synopsis:

```
$PQTMVEHMOT,<MsgVer>,<PeakAcceleration>,<PeakAngularRate>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgVer>	Numeric	-	Message version. 1 = Version 1 (Always 1 for this version.)
<PeakAcceleration>	Numeric	m/s ²	Peak acceleration of vehicle.
<PeakAngularRate>	Numeric	deg/s	Peak angular rate of vehicle.

Example:

```
$PQTMVEHMOT,1,0.288124,0.159930*0A
```

NOTE

This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for four-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.11. PQTMSENMSG

Outputs sensor information.

Type:

Output

Synopsis:

```
$PQTMSENMSG,<MsgVer>,<TimeStamp>,<Par1>[,<Par2>,...,<ParN>]*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgVer>	Numeric	-	Message version. 4 = IMU sensor data matching vehicle reference frame. See Figure 1: Reference Frame for details.
<TimeStamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer.
<Par1> to <ParN>	Numeric	-	Sensor information. See Chapter 3.1.11.1 If <MsgVer> = 4 for details.

3.1.11.1. If <MsgVer> = 4

Synopsis:

```
$PQTMSENMSG,4,<TimeStamp>,<IMU_Temp>,<IMU_GYRO_X>,<IMU_GYRO_Y>,<IMU_GYRO_Z>,<IMU_ACC_X>,<IMU_ACC_Y>,<IMU_ACC_Z>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<TimeStamp>	Numeric	Millisecond	Timestamp since power-on. 32-bit unsigned integer.
<IMU_Temp>	Numeric	Celsius	IMU temperature.
<IMU_GYRO_X>	Numeric	dps	IMU X-axis gyro value.
<IMU_GYRO_Y>	Numeric	dps	IMU Y-axis gyro value.
<IMU_GYRO_Z>	Numeric	dps	IMU Z-axis gyro value.
<IMU_ACC_X>	Numeric	g	IMU X-axis accelerometer value.

Field	Format	Unit	Description
<IMU_ACC_Y>	Numeric	g	IMU Y-axis accelerometer value.
<IMU_ACC_Z>	Numeric	g	IMU Z-axis accelerometer value.

Example:

```
$PQTMSENMSG,4,1977253,29.830917,1.727613,0.015743,0.804347,-0.250096,-0.467039,10.444151*24
```

NOTE

This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for four-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.12. PQTMCFGDRRTD

Sets/gets the DR running time and distance in DR only mode. If the running time or distance of the receiver exceeds the set values, the receiver will exit GNSS + DR or DR only mode.

Type:

Set/Get

Synopsis:

```
//Set:  
$PQTMCFGDRRTD,W,<Time>,<Dist>*<Checksum><CR><LF>  
//Get:  
$PQTMCFGDRRTD,R*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Time>	Numeric	Second	Configuration of DR running time. <u>0</u> = No limitation
<Dist>	Numeric	Meter	Configuration of DR running distance. <u>0</u> = No limitation

Result:

- If successful, the module returns:

```
//Set:  
$PQTMCFGDRRTD,OK*<Checksum><CR><LF>  
//Get:  
$PQTMCFGDRRTD,OK,<Time>,<Dist>*<Checksum><CR><LF>
```

- If failed, the module returns:

```
$PQTMCFGDRRTD,ERROR,<ErrCode>*<Checksum><CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
//Set:  
$PQTMCFGDRRTD,W,600,10000*72  
$PQTMCFGDRRTD,OK*26  
//Get:  
$PQTMCFGDRRTD,R*70  
$PQTMCFGDRRTD,OK,600,10000*21
```

3.1.13. PQTMCFGIMUTC

Sets/gets the IMU temperature compensation feature.

Type:

Set/Get

Synopsis:

```
//Set:  
$PQTMCFGIMUTC,W,<State>*<Checksum><CR><LF>  
//Get:  
$PQTMCFGIMUTC,R*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<State>	Numeric	-	State of IMU temperature compensation feature. <u>0</u> = Disabled <u>1</u> = Enabled

Result:

- If successful, the module returns:

```
//Set:  
$PQTMCFGIMUTC,OK*<Checksum><CR><LF>  
//Get:  
$PQTMCFGIMUTC,OK,<State>*<Checksum><CR><LF>
```

- If failed, the module returns:

```
$PQTMCFGIMUTC,ERROR,<ErrCode>*<Checksum><CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
//Enable temperature compensation feature.  
$PQTMCFGIMUTC,W,1*7A  
$PQTMCFGIMUTC,OK*34  
  
//Query temperature compensation state.  
$PQTMCFGIMUTC,R*62  
$PQTMCFGIMUTC,OK,1*29
```

3.1.14. PQTMDRPVA

Outputs the DR position, velocity and attitude.

Type:

Output

Synopsis:

```
$PQTMDRPVA,<MsgVer>,<Timestamp>,<Time>,<SolType>,<Lat>,<Lon>,<Alt>,<Sep>,<VelN>,<VelE>,<  
VelD>,<Spd>,<Roll>,<Pitch><Heading>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<MsgVer>	Numeric	-	Message version. 1 = Version 1 (Always 1 for this version.)
<Timestamp>	Numeric	Millisecond	Milliseconds since module turn-on. 32-bit unsigned integer.

Field	Format	Unit	Description
<Time>	hhmmss.sss	-	UTC time. hh: Hours (00–23) mm: Minutes (00–59) ss: Seconds (00–59) sss: Decimal fraction of seconds
<SolType>	Numeric	-	Solution type. 0 = No fix 1 = GNSS only 2 = Combination (GNSS + DR) 3 = DR only
<Lat>	Numeric	Degree	Latitude. Note that this field is empty in case of an invalid value.
<Lon>	Numeric	Degree	Longitude. Note that this field is empty in case of an invalid value.
<Alt>	Numeric	Meter	Altitude above mean-sea-level. Note that this field is empty in case of an invalid value.
<Sep>	Numeric	Meter	Geoidal separation (the difference between the WGS84 earth ellipsoid surface and the mean-sea-level surface). Note that this field is empty in case of an invalid value.
<VelN>	Numeric	m/s	North velocity. Note that this field is empty in case of an invalid value.
<VelE>	Numeric	m/s	East velocity. Note that this field is empty in case of an invalid value.
<VelD>	Numeric	m/s	Down velocity. Note that this field is empty in case of an invalid value.
<Spd>	Numeric	m/s	Ground speed. Note that this field is empty in case of an invalid value.
<Roll>	Numeric	Degree	Roll angle. Note that this field is empty in case of an invalid value. Range: -180.000000 to 180.000000
<Pitch>	Numeric	Degree	Pitch angle. Note that this field is empty in case of an invalid value. Range: -90.000000 to 90.000000
<Heading>	Numeric	Degree	Heading. Note that this field is empty in case of an invalid value. Range: 0.000000–360.000000

Example:

```
//No fix.  
$PQTMDRPVA,1,1000,163355.000,0,,,,,,,,,*7C  
  
//GNSS + DR fix.  
$PQTMDRPVA,1,75000,083737.000,2,31.12738291,117.26372910,34.212,5.267,3.212,2.928,0.238,4.3  
46,0.392663,1.300793,0.030088*5E
```

3.1.15. PQTMCFGDRHOT

Sets/gets the DR hot start feature.

Type:

Set/Get

Synopsis:

```
//Set:  
$PQTMCFGDRHOT,W,<Mode>*<Checksum><CR><LF>  
//Get:  
$PQTMCFGDRHOT,R*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Mode>	Numeric	-	<p>Enable/disable the DR hot start mode.</p> <p>0 = Disable DR hot start. DR needs to be recalibrated after each power-up.</p> <p>1 = Enable DR hot start. DR does not need to be recalibrated after each power-up, and the module outputs position information immediately after power-up in the case of no signal.</p> <p>2 = Enable DR hot start. DR does not need to be recalibrated after each power-up, but the module does not output position information after power-up in the case of no signal.</p>

Result:

- If successful, the module returns:

```
//Set:  
$PQTMCFGDRHOT,OK*<Checksum><CR><LF>  
  
//Get:  
$PQTMCFGDRHOT,OK,<Mode>*<Checksum><CR><LF>
```

- If failed, the module returns:

```
$PQTMCFGDRHOT,ERROR,<ErrCode>*<Checksum><CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
//Set:  
$PQTMCFGDRHOT,W,1*79  
$PQTMCFGDRHOT,OK*37  
  
//Get:  
$PQTMCFGDRHOT,R*61  
$PQTMCFGDRHOT,OK,1*2A
```

NOTE

This message is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for four-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

3.1.16. PQTMCFGDR

Sets/gets the DR state.

Type:

Set/Get

Synopsis:

```
//Set:  
$PQTMCFGDR,W,<State>*<Checksum><CR><LF>  
  
//Get:  
$PQTMCFGDR,R*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<State>	Numeric	-	Enable/disable the DR feature. 0 = Disable DR feature <u>1</u> = Enable DR feature

Result:

- If successful, the module returns:

```
//Set:  
$PQTMCFGDR,OK*<Checksum><CR><LF>  
//Get:  
$PQTMCFGDR,OK,<State>*<Checksum><CR><LF>
```

- If failed, the module returns:

```
$PQTMCFGDR,ERROR,<ErrCode>*<Checksum><CR><LF>
```

For details about <ErrCode>, see [Table 2: Error Codes](#).

Example:

```
//Set:  
$PQTMCFGDR,W,1*2A  
$PQTMCFGDR,OK*64  
//Get:  
$PQTMCFGDR,R*32  
$PQTMCFGDR,OK,1*79
```

3.2. PAIR Messages

This chapter explains DR related PAIR messages (proprietary NMEA messages defined by the chipset supplier). “P” means proprietary message, “AIR” means the command defined by the chipset supplier.

3.2.1. Packet Type: 6010 PAIR_CUSTOM_SET_MSG_OUTPUT

Enables/disables the output of **\$PQTMVEHMSG**, **\$PQTMSENMSG**, **\$PQTMDRCAL**, **\$PQTMIMUTYPE** and **\$PQTMVEHMOT** messages.

Type:

Set

Synopsis:

```
$PAIR6010,<Type>,<Output_State>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Type>	Numeric	-	Message type. -1 = Reset output state of all following sentence types to the default value 0 = \$PQTMVEHMSG (Default: disabled) 1 = \$PQTMSENMSG (Default: disabled) 2 = \$PQTMDRCAL (Default: disabled) 3 = \$PQTMIMUTYPE (Default: enabled) 4 = \$PQTMVEHMOT (Default: disabled)
<Output_State>	Numeric	-	Message output state. 0 = Disabled 1 = Enabled

Result:

Returns **\$PAIR001** message. See [document \[2\] protocol specification](#) for details.

Example:

```
$PAIR6010,0,1*0C
$PAIR001,6010,0*0C
```

NOTE

1. Send **\$PQTMSAVEPAR*5A** and reset the module for **\$PAIR6010** to take effect.
2. The output rate of **\$PQTMVEHMSG** and **\$PQTMSENMSG** is always 10 Hz. The output rate of **\$PQTMDRCAL** and **\$PQTMVEHMOT** depends on position fix rate. **\$PQTMIMUTYPE** is only output once after each boot-up.

3.2.2. Packet Type: 6011 PAIR_CUSTOM_GET_MSG_OUTPUT

Gets whether the output of **\$PQTMVEHMSG**, **\$PQTMSENMSG**, **\$PQTMDRCAL**, **\$PQTMIMUTYPE** and **\$PQTMVEHMOT** messages is enabled.

Type:

Get

Synopsis:

```
$PAIR6011,<Type>*<Checksum><CR><LF>
```

Parameter:

Field	Format	Unit	Description
<Type>	Numeric	-	Message type. 0 = \$PQTMVEHMSG 1 = \$PQTMSENMSG 2 = \$PQTMDRCAL 3 = \$PQTMIMUTYPE 4 = \$PQTMVEHMOT

Result:

Returns **\$PAIR001** message and query result. See [document \[2\] protocol specification](#) for details.

Query result message format:

```
$PAIR6011,<Type>,<Output_State>*<Checksum><CR><LF>
```

Parameters included in the result:

Field	Format	Unit	Description
<Type>	Numeric	-	Message type. 0 = \$PQTMVEHMSG 1 = \$PQTMSENMSG 2 = \$PQTMDRCAL 3 = \$PQTMIMUTYPE 4 = \$PQTMVEHMOT
<Output_State>	Numeric	-	Message output state. 0 = Disabled 1 = Enabled

Example:

```
$PAIR6011,1*11
$PAIR001,6011,0*0D
$PAIR6011,1,0*0D
```

NOTE

This command is only supported by LC29H (BA) and LC29H (CA) with software versions dedicated for four-wheel vehicles. Contact Quectel Technical Support (support@quectel.com) for details about the software versions.

4 Appendix A References

Table 3: Related Documents

Document Name
[1] Quectel LC29H Series Hardware Design
[2] Quectel LC29H Series&LC79H(AL) GNSS Protocol Specification

Table 4: Terms and Abbreviations

Abbreviation	Description
ARP	Antenna Reference Point
BDS	BeiDou Navigation Satellite System
DR	Dead Reckoning
Galileo	Galileo Satellite Navigation System (EU)
GLONASS	Global Navigation Satellite System (Russian)
C/N ₀	Carrier-to-Noise-Density Ratio
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
IMU	Inertial Measurement Unit
MSM	Multiple Signal Message
NMEA	NMEA (National Marine Electronics Association) 0183 Interface Standard
PQTM	Proprietary Protocol of Quectel
QZSS	Quasi-Zenith Satellite System
RTCM	Radio Technical Commission for Maritime Services
RTK	Real-Time Kinematic

5 Appendix B Special Characters

Table 5: Special Characters

Special Character	Definition
<CR>	Carriage return character.
<LF>	Line feed character.
<...>	Parameter name. Angle brackets do not appear in the message.
[...]	Optional field of a message. Square brackets do not appear in the message.
{...}	Repeated field of a message. Curly brackets do not appear in the message.
<u>Underline</u>	Default setting of a parameter.